



OPTIK LED

SWP-Slim Line Wall Pack

Project Information _____

Type _____

Name _____

Voltage _____

Product Description

OPTIK LED slim line wall led luminaire has a beautiful low profile design intended for outdoor wall mounted applications, combines the latest in LED technology including weather-tight Ip65 LED driver and thermal management. High-performance illumination that lasts 50,000HRS. It's ideal for replacing 150-200W HID, with typical energy savings of 80%.



Application

Outdoor Lighting Area Lights .



OP-SWP	25W	40K	50K	110-120LM/W	U 120-277V	T-Black
	45W	40K	50K	110-120LM/W	HV 347V, 480V	Z-Bronze
	75W	40K	50K	110-120LM/W		

Electric Characteristic

Specification/Model	OP-SWP-25W-K		OP-SWP-45W-K			OP-SWP-75W-K
LED Chips	SAMSUNG 3535					
Input power	250W		45W			75W
Lumens output	3000LM		5400LM			9000LM
Efficiency	120LM/W		120LM/W			120LM/W
CRI	>72Ra					
Color Temperature	5000K					
Input voltage	100-277V/280-520V					
Light distribution type	Full Cut Off					
Working temperature	-30+60°C					
Junction temperature	<75°C					
lamps efficiency	≥90%					
Certificate	ETL,cETL,DLC					
Equivalent	70W MH/HPS		100W MH/HPS			150W MH/HPS

Ordering Information

Example: OP-SWP-45W-4K-N

Product	Power	Replacement	Color Temperature	Photocell	Furnish	Head connector
OP-SWP-25W	3 module	70W MH/HPS	40K 4000K	N not photocell	Z-Bronze	
OP-SB-150W	3 module	100W MH/HPS				
OP-SB-240W	3 module	150W MH/HPS	50K 5000K	Y yes photocell		



Projected LED Lumen Maintenance

Operating hours	0	25000	50000
Lumen	1	0.91	0.8

Data references the extrapolated performance projections for the SHOEBOX LED platform in a 25°C ambient, based on 10,000 hours of LED testing (tested per IESNA LM-80-08 and projected per IESNA TM-21-11).

After-sale Service

Please use licensed electrical contractor for installation. Please contact OPTIK LED for warranty details.

NOTE: Actual performance may differ as a result of end-user environment and application. All values are without notice.